

Nautilus Hyosung 2700A ATM



Specifications

Dimensions (CEN-I base)

- Height: 1423.56mm (56.4")
- Width: 398.78mm (15.7")
- Depth: 584.2mm (23")
- Weight: 129.99kg (286.6lbs)

Environmental Conditions

- Temperature: 32°F – 104°F
(0°C ~ 40°C)
- Humidity 20% – 85%

System Platform

- Microsoft Windows®
CE6.0 platform

Customer Interface

- 12.1" wide color TFT LCD
- Input type – 4x3 touch function keys, PCI compliant EPP, T-DES, DES, RSA
- Card Reader - DIP hybrid, EMV level 1,2 complaint, anti-skimming (optional)
- Audio jack

Media Handling

- **1,000 notes cassette**
- **2,000 notes cassette (up to 3)**

Security

- Safe – UL291
- Electronic combination lock
- Cencon or S&G audit locks (optional)
- Security camera (optional)
- EPP privacy shield

Printer

- 80mm graphical thermal receipt printer

Power Supply

- AC 100V ~ 240V, 50-60 Hz

Additional Features

- Lead-through indicator
- Speaker
- NFC reader (optional)
- Communication – TCP/IP, wireless



Address:

Unit 5/48 Export Drive
Molendinar
QLD Australia 4214

Phone: 0411 422 291

Fax: 07 5571 5160

Postal:

PO Box 1311
Paradise Point
QLD Australia 4216

www.completeatmservices.com.au