

Driving tomorrow's technology.

Monimax NH2700

The **Monimax NH2700™** is specially designed to provide a reliable and cost-effective ATM solution for the retail and independent ATM deployer markets. With one of the smallest footprints, and available in both indoor lobby and fully-weatherised through-the-wall models, the **Monimax NH2700** offers flexible installation options. Built around the stable and cost-effective Windows CE platform, the **Monimax NH2700** is designed to operate day-in day-out with the minimum of maintenance.

Maximum visibility

Many retail ATMs rely on being seen to attract transactions. The **Monimax NH2700** features one of the largest standard screens available with a large 10.2" widescreen.

Designed for maximum uptime

The **Monimax NH2700** has been designed to provide the highest levels of ATM whilst operating in the most demanding retail environments. Able to integrate into a range of remote monitoring platforms, the **Monimax NH2700** is designed to permit fast repairs and maintenance – delivering a dependable ATM service for your customers..

Flexibility to meet the needs of the future

The **Monimax NH2700** features an open architecture modular design providing the flexibility to take advantage of current and future capabilities including touch screens, barcode readers, and contactless card readers.

Flexible Security & Installation Options

The **Monimax NH2700** is available in either business hours or Level 1 safe configurations; and in both lobby and through-the-wall options – allowing you to offer a full range of installation solutions to suit your cash service requirements and installation needs.



MONIMAX™

Driving tomorrow's technology.

Monimax NH2700 specifications

System Control

- Microsoft Windows CE
- NH Terminal handler, Triton messages

Communication

- TCP/IP

Customer Display

- 10.2" wide TFT LCD
- 1024 X 600

Supervisor panel

- 8" Wide TFT LCD (TTW Option)
- Touch Screen

Input Type

- 4 X 2 Soft touch function keys
- PCI EPP, T-DES, DES, RSA

Security

- UL Business Hour, UL-291 Level-1
- Mechanical combination lock
- KABA Mas cencon lock option
- Time delay lock option

Card Reader

- Hybrid DIP
- EMV 1,2 compliant
- Anti-skimming enhancement device option

Printer

- 80mm Graphic thermal receipt printer
- Electric Journal

Cash Dispenser

- 2 Cassettes Cash dispenser
 - 200 notes reject bun capacity
 - 40 notes dispense max per transaction
 - 2,000 notes per cassette capacity
- Up to 3 Cassettes

Additional Features

- LED Topper
- 15" LCD Topper
- ADA earphone jack with volume controller
- TTW Wall collar
(Supports 200mm wall thickness)

Power Supply

- AC110-230VAC, 50-60Hz

Dimension

- Height: 1,300mm
- Width: 410mm
- Depth: 580mm
- Weight: 125Kg (Business Hour)
290Kg (Level-1)



MONIMAX™

 NH AUSTRALIA